

FLOOR PROTECTION BOARD

Part Nbr. 42008

BODENSCHUTZSYSTEME

Relegasse 2, 1190 Wien

office@rele.at • www.rele.at



International / Austria



RELE

TECHNICAL DETAILS:

Taking into account business and technical aspects, the best solution for manufacturing is using Polyolefin, the Äthylen-Propylen Copolymer; The PP – hollow cell board with cellular structure is manufactured using extrusion technology with a wide slot nozzle.

The board consists of two long flat layers, interconnected through parallel and vertical ribs. The boards are 0,4 to 0,5 mm (0,015" – 0,019") thick, and the ribs have a distance to each

other of 5 to 6 mm (0,19" – 0,23"), overall thickness of the board 4 mm (0,15"), weight 1200g / m²

PACKAGING:

1 Euro- Palette (220 pcs.) ~180m² / 1937 sqft.

Weight: 230 kg/ 507lbs including Euro-pallet

Measurements: L1200mm x W800mm x H1000mm

(L47,24" x W31,49" x H39,37")



INSTALLATION:

1. During shipping staple boards according to cut
2. Ensure floor is properly cleaned before installation
3. Start installation from one end, print upside
4. Boards can easily be cut with a knife to fit around columns and edges
5. Use proper tape to tape boards together in order to prevent edges from standing up
6. Removal: Tape can be removed without leaving any stains on the boards.
Staple boards according to cut to save time during cleaning process
7. Clean with high pressure water only (no chemicals); hang up for drying



For all our services and products please refer to our AGB

www.rele.at



PRODUCT DESCRIPTION:

- Board made out of Polypropylene
- 48,25" x 31,50" / 1.200gsm. // 1200mm x 800 mm x 4mm. / 1.200gr
- Grade 0,157" / 4mm
- With 0,157" / 4mm hollow-cell technology, die cut,
- Color: white transparent, print on request (minimum order 15 pallets)

FEATURES:

- excellent stiffness, pressure resistance, resistance towards dynamic load – (..rolling scaffolds),
- foldable, easy to cut, suitable for printing, easy to clean, free of taste
- and odor / smell & non-hazardous to health, reusable, recyclable

RANGE OF APPLICATION:

- Textile floor coverings (needle felt, velour)
- Linoleum, PVC- floors
- Wooden floor,
- Stone - Tiles- screed

ADVANTAGES:

- protects all kind of floors,
- shortens the construction time,
- easy recognition of floor installation if white transparent board is used
- low weight, (2,2lbs / 1kg. per board), stackable & reusable

RESISTANCE:

- Moisture, Chemicals and Cold

STORAGE:

- Between -10°C bis +90°C / 14°F and 194°F
- protect boards from direct UV
- laying on flat surface